

# Eco Chemical TempLine Clear Base

## PRODUCT DESCRIPTION

TempLine Clear Base is a primer coating developed to pre-coat synthetic fibers before painting lines and logos on the synthetic turf field. Clear Base enables turf paint to adhere better to the synthetic fibers and facilitates the removal of paint that might otherwise stick to worn fibers and inlaid lines. Clear Base is recommended especially when paints are applied over the top of light-colored inlaid lines and logos. TempLine Clear Base is easy to apply, has low VOC's, cleans up with soap and water, and is easy to remove with TempLine Remover solutions.

Surface types: Safe for use on any type of synthetic turf and most infill systems.

## APPLICATION INSTRUCTIONS

1. Make sure the turf surface is clean and dry.
2. Stir well before and periodically during application.
3. Apply with conventional air or airless spray equipment, at temperatures between 45° and 95° F. Recommend tip size of 317 or 319 for 4" lines.
4. Clean equipment with warm soapy water immediately after use according to equipment manufacturers guidelines. TempLine Remover LV can also be used to clean equipment.
5. Allow lines to fully dry (24 hour dry time is recommend) before applying the paint top coat.

## STORAGE

Close container after each use. KEEP FROM FREEZING.

## DISPOSAL

Never pour leftover material down any drain or sink. Use up material on the job, or seal pail and store safely for future use. Do not incinerate closed containers. For specific disposal guidelines, contact your local waste management agency.

## TECHNICAL DATA

<b>Product</b>	Eco TempLine Clear Base
<b>Approximate dry time at 70° F.</b>	Dry to touch in 2 to 4 hours. Suggested dry time before applying topcoat is 24 hours. Note that drying times will vary depending on ambient temperature, humidity, and moisture content of the field.
<b>Coverage</b>	115-165 sq. ft. per gallon or 350-500 linear ft. per gallon for a 4" wide line
<b>Cautions</b>	<ul style="list-style-type: none"> <li>* Do not take internally.</li> <li>* Close container after use.</li> <li>* Use with adequate ventilation. If spraying, use an approved NIOSH/ MSHA respirator.</li> <li>* Keep out of reach of children.</li> </ul> <p>DO NOT FREEZE.</p>
<b>Weight</b>	8.15 to 8.45 lbs per gallon
<b>Viscosity</b>	1000 -1200 cps
<b>pH</b>	8.5 - 9.5
<b>Dilution</b>	No dilution necessary
<b>Odor</b>	Slight
<b>Available</b>	5 gal. pails, 55 gal. drums, or 275 gal. totes

### • TECHNICAL SERVICES INFORMATION

For technical assistance, or to place an order, contact us at (800)-677-7930 or at [customerservice@ecochemical.com](mailto:customerservice@ecochemical.com)

### • LIMITED WARRANTY

If the product is defective, purchaser's exclusive and sole remedy is limited to return of product and repayment of the price, or replacement of defective product. Eco bears no liability for any consequential damages. There are no additional warranties which extend beyond the face hereof.