

Eco Chemical TempLine Premium Grass Paint



PRODUCT DESCRIPTION

Eco TempLine Premium Grass Paint is our highest quality, most durable product for line marking and logo painting on any type of natural grass field. Concentrated formula yields 10 gallons of paint from one 5 gallon pail. The ultra-concentrated formula can be diluted up to 3:1 giving you the flexibility to control the line appearance and the economy. TempLine Premium Grass paint delivers exceptional brightness and opacity at a competitive price. Premium Grass is easy to apply, has low VOC's, and cleans up easily with soap and water.

Surface types: Great for any type of natural grass field.

Color options: Available in 10 standard colors and white. Custom colors available upon request.

APPLICATION INSTRUCTIONS

1. Make sure the field surface is clean, dry and free of debris. Pre-test product on an inconspicuous area.
2. Air and surface temperature should be between 45° - 95° F.
3. Apply with conventional striping methods including air or high pressure airless spray equipment, or wheel transfer line marker. Can also be applied with roller and brush. If using a sprayer, recommended tip size for 4" lines: 317 or 319.
4. Open pail of TempLine Premium and stir well.
5. To dilute, pour half of the contents of the TempLine Premium paint into an empty 5 gallon pail.
6. Fill both pails with water till the level of paint is roughly two inches below the top rim of the pail.
7. Stir both pails till mixture is fully incorporated.
8. Load into your sprayer and you are ready to paint.
9. Clean equipment with water immediately after use according to equipment manufacturers guidelines.
10. Allow lines to fully dry before being exposed to weather or game play.

STORAGE

Close container after each use. KEEP FROM FREEZING.

DISPOSAL

Never pour leftover material down any drain or sink. Use up material on the job, or seal pail and store safely for future use. Do not incinerate closed containers. For specific disposal guidelines, contact your local waste management agency.

TECHNICAL DATA	
Product	Eco Chemical TempLine Premium Grass Paint
Approximate dry time at 70° F.	Dries to touch in 1-1/2 to 2 hours. Note that drying times will vary depending on ambient temperature, humidity, and moisture content of the field.
Coverage	115-165 sq. ft. per gallon or 350-500 linear ft. per gallon for a 4" wide line.
Cautions	* Do not take internally. * Close container after use. * Use with adequate ventilation. If spraying, use an approved NIOSH/ MSHA respirator. * Keep out of reach of children. DO NOT FREEZE.
Weight	12.9 - 13.3 lbs. per gallon
Viscosity	25000 - 35000 cps
pH	8.5 - 9.5
Dilution	Dilute with water at 1:1. Can be diluted up to 3:1
Odor	Slight
Available	5 gal. pails and 55 gal. drums

• TECHNICAL SERVICES INFORMATION

For technical assistance, or to place an order, contact us at (800)-677-7930 or at customerservice@ecochemical.com

• LIMITED WARRANTY

If the product is defective, purchaser's exclusive and sole remedy is limited to return of product and repayment of the price, or replacement of defective product. Eco bears no liability for any consequential damages. There are no additional warranties which extend beyond the face hereof.